SENNHEISER

Sonite Rise

Sonite Rise / Sonite Rise Loaner




Technical Data

S Receiver
2 cm³ coupler data


ANSI / ASA S3.22-2014 (R2020)

IEC 60118-0 : 2022

Output sound pressure level



Acoustic gain




Frequency range	<100 Hz - 10,000 Hz				
Total harmonic distortion	500 Hz	800 Hz	1600 Hz	3200 Hz	
	1.5%	2.0%	2.0%	1.0%	
Expected operating time*	20 h				
Equivalent input noise level	19 dBSPL				

M Receiver
2 cm³ coupler data


ANSI / ASA S3.22-2014 (R2020)

IEC 60118-0 : 2022

Output sound pressure level



Acoustic gain



Frequency range	<100 Hz - 10,000 Hz				
Total harmonic distortion	500 Hz	800 Hz	1600 Hz	3200 Hz	
	1.5%	2.0%	2.0%	1.0%	
Expected operating time*	20 h				
Equivalent input noise level	19 dBSPL				

Warnings

⚠ This hearing instrument has an output sound pressure level that can exceed 132 dB SPL. Special care should be taken when fi tting this instrument as there is a risk of impairing the residual hearing of the user.

⚠ Changes or modifi cations to the hearing aid that are not explicitly approved by the manufacturer are not permitted. Such changes may damage the ear or the hearing aid.

⚠ The developed SPL in the ears of children can be substancially higher than in average adults. RECD measured to correct target of fitted OSPL90 is recommended.

ⓘ Data sheet values were measured with a standard receiver. Please note deviation from these values may occur based on individualized custom shell coupling.

* Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment.

General test information

- Specific measurement settings are used. RTS adjustment with volume control
- The device is operating in linear mode
- Low-level expansion is active
- All data obtained are measured with Target measurement settings
- The latency of the audio signal determined according an internal standard is 6.2 ms

CE 0459

Sonova AG
Laubisrütistrasse 28
CH-8712 Stäfa, Switzerland

Sennheiser is a registered trademark of Sennheiser electronic SE & Co. KG and is used under license by Sonova

SENNHEISER

Sonite Rise

Sonite Rise / Sonite Rise Loaner


Technical Data

P Receiver
2 cm³ coupler data


ANSI / ASA S3.22-2014 (R2020)

IEC 60118-0 : 2022

Output sound pressure level



Acoustic gain




Frequency range	<100 Hz - 7,500 Hz				
Total harmonic distortion	500 Hz	800 Hz	1600 Hz	3200 Hz	
	1.0%	1.5%	1.0%	1.0%	
Expected operating time*	20 h				
Equivalent input noise level	19 dBSPL				

UP Receiver
2 cm³ coupler data


ANSI / ASA S3.22-2014 (R2020)

IEC 60118-0 : 2022

Output sound pressure level



Acoustic gain



Frequency range	<100 Hz - 8,000 Hz				
Total harmonic distortion	500 Hz	800 Hz	1600 Hz	3200 Hz	
	1.5%	1.5%	1.0%	1.0%	
Expected operating time*	20 h				
Equivalent input noise level	19 dBSPL				

* Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment.

⚠ Data sheet values were measured with a standardized custom shell. Please note deviation from these values may occur based on individualized acoustic coupling. Special care should be taken for UP-receivers as individual deviation may lead to MPO exceeding 132dB SPL.

CE 0459

Sonova AG
Laubisrütistrasse 28
CH-8712 Stäfa, Switzerland

Sennheiser is a registered trademark of Sennheiser electronic SE & Co. KG and is used under license by Sonova